



Cordless Impact Wrench
TW140D 3/8" (9.5 mm)



More Compact and High Power



Max Fastening Torque

140 N·m

Work volume

on a single full battery charge

M12, 100N·m about



(with
BL1041B)

320 pcs

Delivers 140 N·m (1,240 in.lbs.) of Max Torque in an ultra compact size



161 mm

54 mm



Single LED job light with preglow and afterglow functions



Variable speed control by trigger

Best possible ergonomic handle for screwing applications



A In order to provide maximum thrust to the bit, the top back of the handle is ergonomically designed and widened to perfectly fit the U-shape formed between user's thumb and index finger.

B Ribbed soft grip enables all finger tips to hold the handle securely against the strong rotational force of counter torque even in single-handed operation.



Li-ion Battery & Charging Time Reference, Compatibility Chart

	BL1016 12V max 1.5Ah	*BL1021B 12V max 2.0Ah	*BL1041B 12V max 4.0Ah
DC10SB	22 min	30 min	60 min
DC10WD	50 min	70 min	130 min

Cordless Impact Wrench

TW140D 3/8" (9.5 mm)

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case

Fastening Capacities	Standard Bolt: M8 - M16 (5/16" - 5/8") High Tensile Bolt: M6 - M12 (1/4" - 1/2") 9.5 mm (3/8")
Square Drive	140 N·m (1,240 in.lbs.)
No Load Speed (RPM)	0 - 2,600
Impacts Per Minute (IPM)	0 - 3,200
Max Fastening Torque	161x66x205 mm (6-3/8"x2-5/8"x8-1/8") w/ BL1016/BL1021B:
Dimensions (L x W x H)	w/ BL1041B: 161x66x224 mm (6-3/8"x2-5/8"x8-7/8")
Net weight	1.0 - 1.2 kg (2.3 - 2.7 lbs.)

Standard Equipment : Belt Clip, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201803