

Cordless Ratchet Wrench WR100D 9.5 mm (3/8") / 6.35 mm (1/4")





Cordless ratchet wrench powered by 12V max CXT Li-lon battery





No load speed: 800 min.⁻¹

providing high efficiency fastening.

Compatible with variable sockets with socket adapter







Socket adaptor 9.5 mm(3/8") Part No.191A50-3



Socket adaptor 6.35 mm (1/4")
Part No.191A51-1

Easy to grip ergonomic design The grip diameter is smaller than that of the competitors, providing the same good handling as hand ratchet wrenches.



Can also be used as a hand ratchet wrench

Switch lever





Forward / reverse rotation change

Turn the reversing lever to the A side for clockwise rotation or to the B side for counterclockwise rotation.





Able to tighten 13mm nut onto M8 threaded rod



LED job light

with preglow and afterglow functions



Standard Equipment

Tool bag Part No. 832071-7






Li-ion Battery & Charging Time Reference, Compatibility Chart

*with Battery fuel gauge	BL1016	*BL1021B	*BL1041B
	12V max 1.5Ah	12V max 2.0Ah	12V max 4.0Ah
DC10SB	22 min	30 min	60 min
DC10WD	50	70	130
	min	min	min

Cordless Ratchet Wrench

WR100D 9.5 mm (3/8") / 6.35 mm (1/4")



Capacity	Standard Bolt: M5 - M12 (3/16" - 1/2")
	High Tensile Bolt: M5 - M10 (3/16" - 3/8")
Square Drive	9.5 / 6.35 mm (3/8" / 1/4")
No Load Speed (RPM)	0 - 800
Max Fastening Torque	47.5 N·m (420 in.lbs.)
Max Output	250 W
Vibration Level	2.5 m/s ² or less
Sound Pressure Level	74 dB(A)
Dimensions (L x W x H)	w/BL1016/BL1021B: 341x67x63 mm (13-7/16"x2-5/8"x2-1/2")
	w/BL1041B: 341x67x84 mm (13-7/16"x2-5/8"x3-5/16")
Net weight	1.0 - 1.2 kg (2.3 - 2.7 lbs.)
-	•

Standard Equipment: Socket Adapter, Battery, Charger, Tool bag

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combinations, according to EPTA-Procedure 01/2014, are shown in the table Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan