

Cordless Multi Tool TM30D









Compatible with all OIS accessories (Oscillating Interface System)







Powered by Slide Li-ion Battery of Makita's New 10.8V Platform





Single LED job light

effectively illuminates the tip of accessory in dark,



Variable speed control by dial



Dust extraction system

available as an option for aggressive dust removal in applications with sanding pad.



Li-ion Battery & Charger Time Reference, Compatibility Chart

| CXT | BL1015 10.8V 1.5Ah | BL1020B 10.8V 2.0Ah with Battery fuel gauge | BL1040B 10.8V 4.0Ah with Battery fuel gauge |
|-------------------------|---------------------------|---|---|
| DC10SA for 10.8V | 22 _{min} | 30 _{min} | 60 _{min} |
| DC10W for 10.8V | 50 _{min} | 70min | 130 _{min} |

Battery fuel gauge

(BL1020B, BL1040B)

The power remaining in the battery can be indicated in 4 stages simply by pushing a button.



Battery fuel gauge(4 stage LED)

Forced air cooling system

DC10SA only

- •Stand-by time until the charge starts can be greatly shortened by using charger DC10SA
- equipped with a built-in cooling fan.
 •Effectively cools down every battery cell with the forced air cooling system and the heat sinks.



Cordless Multi Tool TM30D Oscillations per minute (opm) 6,000 - 20,000 Variable Speed Oscillation angle 168mm (6-5/8") Circumference of aring Soft start 88mm (3-1/2") 277x65x98mm Dimensions **Dust Collecting** (L x W x H) (10-7/8"x2-9/16"x3-7/8", 170W Max Output -X- Built-in Job Light BL1020B: 1.1kg (2.4lbs) Net weight BL1040B: 1.2kg (2.7lbs) Carrying Case Standard Equipment: Oscillating multi tool accessories, Hex Wrench, Battery, Fast Charger,

Dust attachment (country-specific), Tool box (country-specific)

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan